

Kirium Wall product codes

	Codes	Example
Family		
Kirium	KIW	KIW
Light Engine		
8 LED	8	16
16 LED	16	
Drive Current		
300mA	0300	0300
500mA	0500	
700mA	0700	
Colour temperature		
2700K	27	27
3000K	30	
4000K	40	
4000K SunLike™	4S	
Distribution		
Narrow (Diamond+ A1)	A1	A1
Medium (Diamond+ A5)	A5	
Wide (Diamond+ C2)	C2	
Glazing		
Clear	C	F
Frosted	F	
Product Colours		
RAL 9016 White	40	DB
RAL 9005 Black	10	
RAL 7035 Light grey	29	
RAL 7046 Mid grey	CF	
RAL 9006 Aluminium	26	
RAL 9007 Metallic grey	27	
DB 703 Metallic dark grey	DB	
Corten brown	CB	
Mounting		
Standard wall mounting (no BESA conduit)	NB	NB
For mounting over horizontal BESA conduit box	B	
Control		
No photocell	N	IUC
Photocell 35 lux (1:0.5)	U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
Integral CMS - Urban Control	IUC	
Integral CMS - Telensa	ITE	
Integral CMS - Mayflower	IMA	
<i>Pre-programmed dimming [1]</i>		
Presence detector		
Presence detector	PD	-
Emergency version		
3-hour emergency	EM	-
Example code = KIW 016 0300 27 A1 F DB NB IUC		

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)