

Sephora product codes

			Codes	Example
Family				
Sephora			SEP	SEP
Style				
Radius			RA	RA
Cubis			CU	
Size				
450			45	HA
		650	65	
		Halo	HA	
Mounting				
Ø42 Side entry	Ø42 Side entry	Ø42 Side entry	42SE	CDPI
Ø76 Direct post	Ø76 Direct post	Ø76 Direct post	76DP	
Ø76 Post top			76PT	
	Ø114 Post top		11PT	
		Curved direct post (internal)	CDPI	
		Curved direct post (external)	CDPE	
Light engine				
Performance			PE	PE
Colour temperature				
2700K			27	27
3000K			30	
4000K			40	
Distribution				
Wide road - Diamond+ A Optic (A1)			A1	C3
Footpath - Diamond+ B Optic (B1)			B1	
Area - Diamond+ C Optic (C2 / C3)			C2 / C3	
Standard road - Diamond+ D Optic (D1)			D1	
Drive current				
The Performance engine is constant current and can be run at drive currents from 75mA to 800mA are available in 25mA increments.				080
Insert drive current in 3-digit format			eg 250mA = 250	
Product colours				
RAL 9016 White			40	DB
RAL 9005 Black			10	
RAL 7035 Light grey			29	
RAL 7046 Mid grey			CF	
RAL 9006 Aluminium			26	
RAL 9007 Metallic grey			27	
DB 703 Metallic dark grey			DB	
Corten brown			CB	
Control				
No photocell			N	A4
Photocell 35 lux (1:0.5)			U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)			A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)			D8	
3 pin NEMA (not compatible with Halo version)			E	
5 pin NEMA (not compatible with Halo version)			C3	
7 pin NEMA (not compatible with Halo version)			D2	
Pre-programmed dimming [1]				
CMS compatible [1]				
SR Ready [1]				
Example code = SEP RA HA CDPI PE 27 C3 080 DB A4				

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)