

Model	Colour Temperature (select)	Number of LEDs																		Average Efficacy (lm/W)	
				250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000		1050
Daytona	4000K	8	lm	1044	1234	1418	1596	1769	1936	2097	2253	2403	2547	2686	2819	2947	3069	3185	3297	3402	159
			W	6	7	8	9	10	12	13	14	15	16	17	19	20	21	22	24	25	
			lm/W	174	176	177	177	177	161	161	161	160	159	158	148	147	146	145	137	136	
		16	lm	2047	2420	2781	3130	3469	3769	4112	4417	4711	4994	5266	5527	2778	6017	6246	6464	6671	157
			W	11	13	16	18	20	22	24	27	29	31	34	36	38	41	43	46	48	
			lm/W	186	186	174	174	173	171	171	164	162	161	155	154	73	147	145	141	139	
		24	lm	2969	3509	4032	4539	5030	5504	5962	6405	6831	7241	7636	8015	8378	8725	9057	9373	9673	157
			W	17	20	23	27	30	33	37	40	43	47	50	54	57	61	65	68	72	
			lm/W	175	175	175	168	168	167	161	160	159	154	153	148	147	143	139	138	134	
		32	lm	4416	5205	5972	6718	7441	8142	8821	9477	10109	10719	11305	11868	12406	12921	13411	13876	14316	175
			W	23	27	31	35	40	44	48	53	57	62	67	71	76	81	85	90	95	
			lm/W	192	193	193	192	186	185	184	179	177	173	169	167	163	160	158	154	151	
Average Efficacy (lm/W)				182	183	180	178	176	171	169	166	165	162	159	154	133	149	147	142	140	

Based on A2 optic data.

3000K and 2700K lumen outputs are calculated by applying an LOR to published 4000K data.

Check values against photometry file for actual lumen output.

Maximum Efficacy (lm/W)	193
-------------------------	-----

Light Output Reduction Factors	4000K	1.00
	3000K	0.91
	2700K	0.89