

Ely product codes

								Codes	Example
Model									
Ely A		Ely B		Ely C				EA	EB
								EB	
								EC	
Mounting									
Pendant Easyfit™		Pendant Easyfit™		Pendant Easyfit™				E	E
Pendant Threaded		Pendant Threaded		Pendant Threaded				T	
		U bracket square		U bracket square				UBS	
		U bracket tear drop		U bracket tear drop				UBT	
Light Engine									
Performance LED		Performance LED		Performance LED					32
		8 LED		8 LED				8	
		16 LED		16 LED				16	
		24 LED						24	
32 LED		32 LED						32	
48 LED								48	
64 LED								64	
Performance CoB		Performance CoB		Performance CoB					
Single CoB		Single CoB		Single CoB				PC	
		Comfort CoB		Comfort CoB					
		Single CoB		Single CoB				CC	
Colour Temperature									
2700K	2700K	2700K	2700K	2700K	2700K	2700K	2700K	27	30
3000K	3000K	3000K	3000K	3000K	3000K	3000K	3000K	30	
4000K	4000K	4000K	4000K	4000K	4000K	4000K	4000K	40	
Distribution									
Roads - Diamond+ A Optic		Roads - Diamond+ A Optic		Roads - Diamond+ A Optic				A1 / A2 / A3 / A5 / A6	A1
Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic				B1 / B2 / B3	
Areas - Diamond+ C Optic		Areas - Diamond+ C Optic		Areas - Diamond+ C Optic				C1 / C2 / C6	
Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic				ZR / ZL / ZF	
Wide Roads - AC1		Wide Roads - AC1		Wide Roads - AC1				AC1	
Pathways BC1		Pathways BC1		Pathways BC1				BC1	
Areas - CC1		Areas - CC1		Areas - CC1				CC1	
Roads - DC1		Roads - DC1		Roads - DC1				DC1	
		Symmetric		Symmetric				SY	
Drive Current									
<p>Drive currents from 250mA to 1050mA are available in 50mA increments Insert drive current value (eg 750mA = 750)</p> <p>Notes Ely A 48/64 LED = 800mA maximum Ely A 32 LED = 900mA maximum Ely B 24/32 LED = 900mA maximum</p>								250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	700
Product Colours									
RAL 9005 Black								10	10
RAL 7016 Anthracite grey								20	
RAL 7037 Dusty grey								21	
RAL 5003 Sapphire blue								30	
RAL 6005 Light moss green								50	
RAL 3005 Wine red								70	
Control									
No photocell								N	U
Miniature Photocell 35 lux (1:0.5)								U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)								A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)								D8	
Integral CMS - Urban Control (Ely A & B only)								IUC	
Integral CMS - Telensa (Ely A & B only)								ITE	
Integral CMS - Mayflower (Ely A & B only)								IMA	
<i>Pre-programmed dimming</i>									
<i>D4i/SR Ready</i>									
Example code = EB E 32 30 A1 700 10 U									

For further help specifying a product, please [contact us](mailto:info@dw-windsor.com)