

LUMINAIRE SPECIFICATION SHEET

Ref:

DW Windsor Ltd // Pindar Road, Hoddeson, Hertfordshire EN11 ODX, UK // www.dwwindsor.com

Product Name | GRP Garda Illuminated Handrail

Mounting Options Stanchion mounted

Output up to 1956lm

Light Source High power LED

Colour Temp | 2700K / 3000K / 4000K / RGBW

CRI >70

Distribution

Symmetric / Asymmetric (refer to module options)

Number of LEDs 1 to 16 (dependant on module)

Power 1.5W to 21W (dependant on module)

Luminaire Efficacy (max) up to 111lm/W Electrical Class | Class | III

Operating Voltage 24-48V AC/DC SELV

Driver Remote PSU (3-hour emergency battery backup

available)

Lifetime 100,000 hours

Operating Temperature -40°C to +50°C

IP Rating IP66

IK Rating IK10

Colour Finish Light grey RAL 7035 / Mid grey RAL 7046 / Black

RAL 9005 (other RAL colours on request)

Housing Material Glass reinforced plastic

Finish Painted

Glazing Material Polycarbonate

Certifications | CE

Control Options Variable resistance dimming / 1-10V dimming /

DALI dimming / DMX (via DALI converter)





Additional Information