

Crieff product codes

| | Codes | Example |
|--|------------------------|---------|
| Family | | |
| Crieff | CRF | CRF |
| Light source | | |
| Performance LED | | |
| 16 LED | PL16 | PL64 |
| 32 LED | PL32 | |
| 64 LED | PL64 | |
| Colour temperature | | |
| 2700K | 27 | 30 |
| 3000K | 30 | |
| 4000K | 40 | |
| Distribution^[1] | | |
| Diamond+ A Optic | A1 / A2 / A3 / A4 / A5 | A1 |
| Diamond+ B Optic | B1 / B2 / B3 / B4 / B5 | |
| Diamond+ C Optic | C1 / C2 / C3 / C4 / C5 | |
| Diamond+ D Optic | D1 / D2 / D3 / D4 / D5 | |
| Diamond+ Z Optic | ZR / ZL / ZF | |
| Drive current^[2] | | |
| 350mA | 0350 | 0500 |
| 500mA | 0500 | |
| 700mA | 0700 | |
| Product colours | | |
| RAL 9005 Black | 10 | 27 |
| RAL 7016 Anthracite grey | 20 | |
| RAL 7037 Dusty grey | 21 | |
| RAL 9007 Textured metallic grey | 27 | |
| RAL 5003 Sapphire blue | 30 | |
| RAL 6005 Light moss green | 50 | |
| Control | | |
| No photocell | N | U |
| Miniature Photocell 35 lux (1:0.5) | U | |
| Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762) | A4 | |
| Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531) | D8 | |
| <i>Pre-programmed dimming^[3]</i> | | |
| <i>CMS compatible^[3]</i> | | |
| <i>SR Ready^[3]</i> | | |
| Example code = CRF PL64 30 A1 0500 27 U | | |

[1] For further information on Diamond+ visit dwwindsor.com/diamond

[2] Other than the standard options shown above, drive currents are available in 50mA increments.

[3] Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)