

DW400 product codes

			Codes	Example
Family				
DW400			DW4	DW4
Mounting				
Direct Entry			D	D
Side Entry			S	
Light source				
Performance LED				
16 LED			PL16	PL32
32 LED			PL32	
	10 LED		PL10	
	15 LED		PL15	
	20 LED		PL20	
	30 LED		PL30	
		Lamp: SON-T / CDO-TT		
		50W	050S	
		70W	070S	
		100W	100S	
		Lamp: CosmoPolis		
		45W	045W	
		60W	060W	
		90W	090W	
Colour temperature				
2700K		n/a	27	40
3000K	3000K		30	
4000K	4000K		40	
Distribution^[1]				
Diamond+ A Optic			A1 / A2 / A3 / A4 / A5	A1
Diamond+ B Optic			B1 / B2 / B3 / B4 / B5	
Diamond+ C Optic			C1 / C2 / C3 / C4 / C5	
Diamond+ D Optic			D1 / D2 / D3 / D4 / D5	
Diamond+ Z Optic			ZR / ZL / ZF	
	Road		RD	
	Residential		RES	
	Footpath		FP	
	Area		AR	
		5/35	A	
		10/10	B	
		31/35	C	
		5/25	D	
Drive current^[2]				
350mA		n/a	0350	0700
500mA			0500	
700mA			0700	
Glazing				
Flat toughened glass			FG	PB
Polycarbonate bowl			PB	
Product colours				
RAL 9005 Black			10	10
RAL 7016 Anthracite grey			20	
RAL 7037 Dusty grey			21	
RAL 5003 Sapphire blue			30	
RAL 6005 Light moss green			50	
Control				
No photocell			N	U
Miniature Photocell 35 lux (1:0.5)			U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elxon regime 762)			A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elxon regime 531)			D8	
3 pin NEMA			E	
5 pin NEMA			C3	
7 pin NEMA			D2	
<i>Pre-programmed dimming^[3]</i>				
<i>CMS compatible^[3]</i>				
<i>SR Ready^[3]</i>				
Example code = DW4 D PL32 40 A1 0700 PB 10 U				

[1] For further information on Diamond+ visit dwwindsor.com/diamond

[2] Other than the standard options shown above, drive currents are available in 50mA increments.

[3] Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)