

Ely product codes

								Codes	Example
Model									
Ely A								EA	EB
		Ely B						EB	
				Ely C				EC	
Mounting									
Pendant Easyfit™		Pendant Easyfit™		Pendant Easyfit™				E	E
Pendant Threaded		Pendant Threaded		Pendant Threaded				T	
		U bracket square		U bracket square				UBS	
		U bracket tear drop		U bracket tear drop				UBT	
Light source									
Performance LED		Performance LED		Performance LED					PL32
16 LED		16 LED		16 LED				PL16	
32 LED		32 LED		32 LED				PL32	
64 LED								PL64	
Performance CoB		Performance CoB		Performance CoB					
Single CoB		Single CoB		Single CoB				PC01	
		Comfort CoB		Comfort CoB					
		Single CoB		Single CoB				CC01	
Colour temperature									
2700K	2700K	2700K	2700K	2700K	2700K	2700K	2700K	27	30
3000K	3000K	3000K	3000K	3000K	3000K	3000K	3000K	30	
4000K	4000K	4000K	4000K		4000K	4000K		40	
Distribution^[1]									
Diamond+ A Optic		Diamond+ A Optic		Diamond+ A Optic				A1 / A2 / A3 / A4 / A5	A1
Diamond+ B Optic		Diamond+ B Optic		Diamond+ B Optic				B1 / B2 / B3 / B4 / B5	
Diamond+ C Optic		Diamond+ C Optic		Diamond+ C Optic				C1 / C2 / C3 / C4 / C5	
Diamond+ D Optic		Diamond+ D Optic		Diamond+ D Optic				D1 / D2 / D3 / D4 / D5	
Diamond+ Z Optic		Diamond+ Z Optic		Diamond+ Z Optic				ZR / ZL / ZF	
A1		A1		A1				A1	
B1		B1		B1				B1	
C1		C1		C1				C1	
D1		D1		D1				D1	
				Symmetric				Symmetric	SY
Drive current^[2]									
350mA								0350	0700
500mA								0500	
700mA								0700	
Product colours									
RAL 9005 Black								10	10
RAL 7016 Anthracite grey								20	
RAL 7037 Dusty grey								21	
RAL 5003 Sapphire blue								30	
RAL 6005 Light moss green								50	
RAL 3005 Wine red								70	
Control									
No photocell								N	U
Miniature Photocell 35 lux (1:0.5)								U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)								A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)								D8	
Integral CMS - Urban Control (Ely A & B only)								IUC	
Integral CMS - Telensa (Ely A & B only)								ITE	
Integral CMS - Mayflower (Ely A & B only)								IMA	
<i>Pre-programmed dimming^[3]</i>									
<i>SR Ready^[3]</i>									
Example code = EB E PL32 30 A1 0700 10 U									

[1] For further information on Diamond+ visit dwwindsor.com/diamond

[2] Other than the standard options shown above, drive currents are available in 50mA increments.

[3] Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)