

Henley product codes

				Codes	Example
Family					
Henley				HEN	HEN
Light source					
Performance LED					PC01
16 LED			PL16		
	Performance CoB				
	Single CoB		PC01		
		Comfort CoB			
		Single CoB		CC01	
Colour temperature					
2700K	2700K	2700K	27	27	
3000K	3000K	3000K	30		
4000K	4000K		40		
Distribution ^[1]					
Diamond+ A Optic			A1 / A2 / A3 / A4 / A5		A1
Diamond+ B Optic			B1 / B2 / B3 / B4 / B5		
Diamond+ C Optic			C1 / C2 / C3 / C4 / C5		
Diamond+ D Optic			D1 / D2 / D3 / D4 / D5		
Diamond+ Z Optic			ZR / ZL / ZF		
	A1		A1		
	B1		B1		
	C1		C1		
	D1		D1		
		Symmetric	SY		
Drive current ^[2]					
350mA			0350	0500	
500mA			0500		
700mA			0700		
Product colours					
RAL 9005 Black			10	10	
RAL 7016 Anthracite grey			20		
RAL 7037 Dusty grey			21		
RAL 5003 Sapphire blue			30		
RAL 6005 Light moss green			50		
RAL 3005 Wine red			70		
Control					
No photocell			N	U	
Miniature Photocell 35 lux (1:0.5)			U		
Part night switching miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)			A4		
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)			D8		
Integral CMS - Urban Control			IUC		
Integral CMS - Telensa			ITE		
Integral CMS - Mayflower			IMA		
Pre-programmed dimming ^[3]					
SR Ready ^[3]					
Example code = HEN PC01 27 A1 0500 10 U					

^[1] For further information on Diamond+ visit dwwindsor.com/diamond

^[2] Other than the standard options shown above, drive currents are available in 50mA increments.

^[3] Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)