

## Kaskara product codes

	Codes	Example
<b>Model</b>		
Kaskara 2	KA2	KA3
Kaskara 3	KA3	
<b>Mounting</b>		
Stirrup bracket (standard)	R	PT
Ø76mm Post top	PT	
<b>Colour temperature</b>		
3000K	30	30
4000K	40	
4000K SUNLIKE	4S	
<b>Distribution</b>		
Narrow	N	W
Wide	W	
<b>Product colours</b>		
RAL 7046 Mid grey	CF	10
RAL 7035 Light grey	29	
RAL 9005 Black	10	
RAL 9016 White	40	
<b>Control</b>		
No photocell	N	N
Miniature Photocell 35 lux (1:0.5)	U	
Part night switching miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
3 pin NEMA	E	
5 pin NEMA	C3	
7 pin NEMA	D2	
Integral CMS - Urban Control	IUC	
Integral CMS - Telensa	ITE	
Integral CMS - Mayflower	IMA	
<i>Pre-programmed dimming [1]</i>		
Example code = KA3 PT 30 W 10 N		

[1] Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)