

Katana product codes

			Codes	Example
Family				
Katana			KAT	KAT
Model				
Urban			U	U
Industrial			I	
Mounting				
Wall			WW	PT
	Post top		PT	
		Direct post	DP	
Module quantity				
1	1	1	1	2
2	2	2	2	
		3	3	
	4		4	
Colour temperature				
2700K			27	30
3000K			30	
4000K			40	
Distribution^[1]				
Diamond+ A Optic - Wide road (A1 / A2 / A3 / A4 / A5)			A1 / A2 / A3 / A4 / A5	A1
Diamond+ B Optic - Narrow road (B1 / B2 / B3 / B4 / B5)			B1 / B2 / B3 / B4 / B5	
Diamond+ C Optic - Area (C1 / C2 / C3 / C4 / C5)			C1 / C2 / C3 / C4 / C5	
Diamond+ D Optic - Standard road (D1 / D2 / D3 / D4 / D5)			D1 / D2 / D3 / D4 / D5	
Diamond+ F1 Optic - Floodlighting (F1)			F1	
Drive current				
Drive currents from 200mA to 1000mA are available in 50mA increments. Insert drive current value in 4-digit format (eg 250mA = 0250)			0200 / 0250 / 0300 / 0350 / 0400 / 0450 / 0500 / 0550 / 0600 / 0650 / 0700 / 0750 / 0800 / 0850 / 0900 / 0950 / 1000	0700
Product colours				
RAL 7046 Mid grey			CF	CF
RAL 7035 Light grey			29	
RAL 9005 Black			10	
Control				
No photocell			N	D2
Photocell 35 lux (1:0.5)			U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)			A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)			D8	
3 pin NEMA			E	
5 pin NEMA			C3	
7 pin NEMA			D2	
<i>Pre-programmed dimming [2]</i>				
<i>CMS compatible [2]</i>				
<i>SR Ready [2]</i>				
Example code = KAT U PT 2 30 A1 0700 CF D2				

[1] For further information on Diamond+ visit dwwindsor.com/diamond

[2] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)