

KIOS 10 (KI-60667)





Luminaire structure

- Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance
- Stainless steel frame
- Single cable entry
- Through wiring on request
- Stainless steel fasteners in grade 316
- High-efficiency PMMA lens
- Durable silicone rubber gasket
- Clear or frosted toughened glass 15mm
- Integral control gear
- Recessing box in high density polyethylene is included
- Suitable for drive-over with a maximum load of 2000 kg
- Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 50 km/h
- Load is transferred by the housing to the foundation
- The distance between the floodlight and the illuminated surface should be at least 0.5 m



Kios 10



Light symbol



T4

Product color



- 00
Stainless Steel

Product description

With recessing box / driver - Embross frame

Technical information

Lamp	16 LED
Lamp type	LED
Dimming type	On/Off, 1-10V, DALI
EEC	A++
Material	Stainless Steel
Weight	11.8 kg

Luminaire	
Power	25 W
Lumen	2426 - 2739 lm
Efficacy	97 - 110 lm/W
CCT	3000K, 4000K
Drive current	500 mA
Optic	T2 [136°x 48°], T3 [136°x 67°], T4 [92°x 73°]

We reserve the right to make technical and design changes.

12:21, 24-01-2020

<https://www.ligman.com/kios-10-ki-60667/>

EUROPE
LIGMAN EUROPE s.r.o.
VGP Park Ústí nad Labem
P 2 120
40317, Přestanov
Czech Republic
+420 477 071 500
sales.cz@ligman.com

ASIA PACIFIC
LIGMAN Lighting Co.,Ltd.
17/2 Moo4 Monthong
Bangnampreaw
24150, Chachoengsao
Thailand
+66 2 108 6700
info@ligman.com

KIOS 10 (KI-60667)**Accessories**



Anti slip glass
A61712



Connector IP68
A62591

KIOS 10 (KI-60667)

Variant reference	Variant name	Lumen (Luminaire)
KI-60667-T2-W30-ND	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 48° - 3000K - On/Off - Stainless Steel	2560 lm
KI-60667-T2-W40-ND	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 48° - 4000K - On/Off - Stainless Steel	2739 lm
KI-60667-T3-W30-ND	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 67° - 3000K - On/Off - Stainless Steel	2426 lm
KI-60667-T3-W40-ND	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 67° - 4000K - On/Off - Stainless Steel	2596 lm
KI-60667-T4-W30-ND	KIOS 10 - KI-60667 - 16 LED - 25 W - 92°x 73° - 3000K - On/Off - Stainless Steel	2469 lm
KI-60667-T4-W40-ND	KIOS 10 - KI-60667 - 16 LED - 25 W - 92°x 73° - 4000K - On/Off - Stainless Steel	2642 lm
KI-60667-T2-W30-DI	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 48° - 3000K - 1-10V - Stainless Steel	2560 lm
KI-60667-T2-W40-DI	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 48° - 4000K - 1-10V - Stainless Steel	2739 lm
KI-60667-T2-W30-DA	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 48° - 3000K - DALI - Stainless Steel	2560 lm
KI-60667-T2-W40-DA	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 48° - 4000K - DALI - Stainless Steel	2739 lm
KI-60667-T3-W40-DA	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 67° - 4000K - DALI - Stainless Steel	2596 lm
KI-60667-T3-W30-DA	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 67° - 3000K - DALI - Stainless Steel	2426 lm
KI-60667-T3-W40-DI	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 67° - 4000K - 1-10V - Stainless Steel	2596 lm
KI-60667-T3-W30-DI	KIOS 10 - KI-60667 - 16 LED - 25 W - 136°x 67° - 3000K - 1-10V - Stainless Steel	2426 lm
KI-60667-T4-W40-DI	KIOS 10 - KI-60667 - 16 LED - 25 W - 92°x 73° - 4000K - 1-10V - Stainless Steel	2642 lm
KI-60667-T4-W30-DI	KIOS 10 - KI-60667 - 16 LED - 25 W - 92°x 73° - 3000K - 1-10V - Stainless Steel	2469 lm
KI-60667-T4-W40-DA	KIOS 10 - KI-60667 - 16 LED - 25 W - 92°x 73° - 4000K - DALI - Stainless Steel	2642 lm
KI-60667-T4-W30-DA	KIOS 10 - KI-60667 - 16 LED - 25 W - 92°x 73° - 3000K - DALI - Stainless Steel	2469 lm

We reserve the right to make technical and design changes.

12:21, 24-01-2020

<https://www.ligman.com/kios-10-ki-60667/>

EUROPE

LIGMAN EUROPE s.r.o.
VGP Park Ústí nad Labem
P 2 120
40317, Přestanov
Czech Republic
+420 477 071 500
sales.cz@ligman.com

ASIA PACIFIC

LIGMAN Lighting Co.,Ltd.
17/2 Moo4 Monthong
Bangnampreaw
24150, Chachoengsao
Thailand
+66 2 108 6700
info@ligman.com