


**KIOS 2 (KI-60505)**





**Luminaire structure**


- Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance
- Stainless steel frame
- Single cable entry
- Through wiring on request
- Stainless steel fasteners in grade 316
- High-efficiency PMMA lens
- Durable silicone rubber gasket
- Clear or frosted toughened glass 15mm
- Integral control gear
- Recessing box in high density polyethylene is included
- Suitable for drive-over with a maximum load of 2000 kg
- Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 50 km/h
- Load is transferred by the housing to the foundation
- The distance between the floodlight and the illuminated surface should be at least 0.5 m




*Kios 2*



**Light symbol**



**Product color**



- 00  
Stainless Steel

**Product description**

With recessing box / driver - Embross frame - 5° or 10° Tilttable

**Technical information**

<b>Lamp</b>	2 x 3 LED
<b>Lamp type</b>	LED
<b>Dimming type</b>	DALI, 1-10V, On/Off
<b>EEC</b>	A++
<b>Material</b>	Stainless Steel
<b>Weight</b>	5.3 kg

<b>Luminaire</b>	
Power	8 W
Lumen	505 - 658 lm
Efficacy	63 - 82 lm/W
CCT	3000K, 4000K
Drive current	350 mA
Optic	M [29°], N [22°], W [50°]

We reserve the right to make technical and design changes.

11:48, 17-01-2020

<https://www.ligman.com/kios-2-ki-60505/>

**EUROPE**  
LIGMAN EUROPE s.r.o.  
VGP Park Ústí nad Labem  
P 2 120  
40317, Přestanov  
Czech Republic  
+420 477 071 500  
[sales.cz@ligman.com](mailto:sales.cz@ligman.com)

**ASIA PACIFIC**  
LIGMAN Lighting Co.,Ltd.  
17/2 Moo4 Monthong  
Bangnampreaw  
24150, Chachoengsao  
Thailand  
+66 2 108 6700  
[info@ligman.com](mailto:info@ligman.com)

**KIOS 2 (KI-60505)****Accessories**

---



---

Anti slip glass  
**A61512**


---



---

Connector IP68  
**A62591**

---



---

Honeycomb louvre  
**A62021**

---

**KIOS 2 (KI-60505)**

Variant reference	Variant name	Lumen (Luminaire)
<b>KI-60505-M-W30-DA</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 29° - 3000K - DALI - Stainless Steel	566 lm
<b>KI-60505-M-W30-DI</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 29° - 3000K - 1-10V - Stainless Steel	566 lm
<b>KI-60505-M-W30-ND</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 29° - 3000K - On/Off - Stainless Steel	566 lm
<b>KI-60505-M-W40-DA</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 29° - 4000K - DALI - Stainless Steel	604 lm
<b>KI-60505-M-W40-DI</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 29° - 4000K - 1-10V - Stainless Steel	604 lm
<b>KI-60505-M-W40-ND</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 29° - 4000K - On/Off - Stainless Steel	604 lm
<b>KI-60505-N-W30-DA</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 22° - 3000K - DALI - Stainless Steel	616 lm
<b>KI-60505-N-W30-DI</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 22° - 3000K - 1-10V - Stainless Steel	616 lm
<b>KI-60505-N-W30-ND</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 22° - 3000K - On/Off - Stainless Steel	616 lm
<b>KI-60505-N-W40-DA</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 22° - 4000K - DALI - Stainless Steel	658 lm
<b>KI-60505-N-W40-DI</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 22° - 4000K - 1-10V - Stainless Steel	658 lm
<b>KI-60505-N-W40-ND</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 22° - 4000K - On/Off - Stainless Steel	658 lm
<b>KI-60505-W-W30-DA</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 50° - 3000K - DALI - Stainless Steel	505 lm
<b>KI-60505-W-W30-DI</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 50° - 3000K - 1-10V - Stainless Steel	505 lm
<b>KI-60505-W-W30-ND</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 50° - 3000K - On/Off - Stainless Steel	505 lm
<b>KI-60505-W-W40-DA</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 50° - 4000K - DALI - Stainless Steel	539 lm
<b>KI-60505-W-W40-DI</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 50° - 4000K - 1-10V - Stainless Steel	539 lm
<b>KI-60505-W-W40-ND</b>	KIOS 2 - KI-60505 - 2 x 3 LED - 8 W - 50° - 4000K - On/Off - Stainless Steel	539 lm

We reserve the right to make technical and design changes.

11:48, 17-01-2020

<https://www.ligman.com/kios-2-ki-60505/>

**EUROPE**

LIGMAN EUROPE s.r.o.  
 VGP Park Ústí nad Labem  
 P 2 120  
 40317, Přestanov  
 Czech Republic  
 +420 477 071 500  
[sales.cz@ligman.com](mailto:sales.cz@ligman.com)

**ASIA PACIFIC**

LIGMAN Lighting Co.,Ltd.  
 17/2 Moo4 Monthong  
 Bangnampreaw  
 24150, Chachoengsao  
 Thailand  
 +66 2 108 6700  
[info@ligman.com](mailto:info@ligman.com)