

KIOS 6 (KI-60791)





Luminaire structure


- Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance
- Stainless steel frame
- Single cable entry
- Through wiring on request
- Stainless steel fasteners in grade 316
- High-efficiency PMMA lens
- Durable silicone rubber gasket
- Clear or frosted toughened glass 15mm
- Integral control gear
- Recessing box in high density polyethylene is included
- Suitable for drive-over with a maximum load of 2000 kg
- Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 50 km/h
- Load is transferred by the housing to the foundation
- The distance between the floodlight and the illuminated surface should be at least 0.5 m




Kios 6



Light symbol



Product color



Product description

With recessing box / driver - Embross frame

Technical information

Lamp	18 LED
Lamp type	LED
Dimming type	On/Off, 1-10V, DALI
EEC	A+
Material	Stainless Steel
Weight	8.9 kg

Luminaire	
Power	30 W
Lumen	2872 - 3160 lm
Efficacy	96 - 105 lm/W
CCT	3000K, 4000K
Drive current	500 mA
Optic	N [16°], M [28°], W [40°]

We reserve the right to make technical and design changes.

12:19, 24-01-2020

<https://www.ligman.com/kios-6-ki-60791/>

EUROPE
 LIGMAN EUROPE s.r.o.
 VGP Park Ústí nad Labem
 P 2 120
 40317, Přestanov
 Czech Republic
 +420 477 071 500
sales.cz@ligman.com

ASIA PACIFIC
 LIGMAN Lighting Co.,Ltd.
 17/2 Moo4 Monthong
 Bangnampreaw
 24150, Chachoengsao
 Thailand
 +66 2 108 6700
info@ligman.com

KIOS 6 (KI-60791)**Accessories**



Anti slip glass
A61612



Connector IP68
A62591

KIOS 6 (KI-60791)

Variant reference	Variant name	Lumen (Luminaire)
KI-60791-N-W30-ND	KIOS 6 - KI-60791 - 18 LED - 30 W - 16° - 3000K - On/Off - Stainless Steel	3092 lm
KI-60791-N-W30-DI	KIOS 6 - KI-60791 - 18 LED - 30 W - 16° - 3000K - 1-10V - Stainless Steel	3092 lm
KI-60791-N-W30-DA	KIOS 6 - KI-60791 - 18 LED - 30 W - 16° - 3000K - DALI - Stainless Steel	3092 lm
KI-60791-N-W40-ND	KIOS 6 - KI-60791 - 18 LED - 30 W - 16° - 4000K - On/Off - Stainless Steel	3130 lm
KI-60791-N-W40-DI	KIOS 6 - KI-60791 - 18 LED - 30 W - 16° - 4000K - 1-10V - Stainless Steel	3130 lm
KI-60791-N-W40-DA	KIOS 6 - KI-60791 - 18 LED - 30 W - 16° - 4000K - DALI - Stainless Steel	3130 lm
KI-60791-M-W30-ND	KIOS 6 - KI-60791 - 18 LED - 30 W - 28° - 3000K - On/Off - Stainless Steel	3122 lm
KI-60791-M-W30-DI	KIOS 6 - KI-60791 - 18 LED - 30 W - 28° - 3000K - 1-10V - Stainless Steel	3122 lm
KI-60791-M-W30-DA	KIOS 6 - KI-60791 - 18 LED - 30 W - 28° - 3000K - DALI - Stainless Steel	3122 lm
KI-60791-M-W40-ND	KIOS 6 - KI-60791 - 18 LED - 30 W - 28° - 4000K - On/Off - Stainless Steel	3160 lm
KI-60791-M-W40-DI	KIOS 6 - KI-60791 - 18 LED - 30 W - 28° - 4000K - 1-10V - Stainless Steel	3160 lm
KI-60791-M-W40-DA	KIOS 6 - KI-60791 - 18 LED - 30 W - 28° - 4000K - DALI - Stainless Steel	3160 lm
KI-60791-W-W30-ND	KIOS 6 - KI-60791 - 18 LED - 30 W - 40° - 3000K - On/Off - Stainless Steel	2872 lm
KI-60791-W-W30-DI	KIOS 6 - KI-60791 - 18 LED - 30 W - 40° - 3000K - 1-10V - Stainless Steel	2872 lm
KI-60791-W-W30-DA	KIOS 6 - KI-60791 - 18 LED - 30 W - 40° - 3000K - DALI - Stainless Steel	2872 lm
KI-60791-W-W40-ND	KIOS 6 - KI-60791 - 18 LED - 30 W - 40° - 4000K - On/Off - Stainless Steel	2907 lm
KI-60791-W-W40-DI	KIOS 6 - KI-60791 - 18 LED - 30 W - 40° - 4000K - 1-10V - Stainless Steel	2907 lm
KI-60791-W-W40-DA	KIOS 6 - KI-60791 - 18 LED - 30 W - 40° - 4000K - DALI - Stainless Steel	2907 lm

We reserve the right to make technical and design changes.

12:19, 24-01-2020

<https://www.ligman.com/kios-6-ki-60791/>

EUROPE

LIGMAN EUROPE s.r.o.
 VGP Park Ústí nad Labem
 P 2 120
 40317, Přestanov
 Czech Republic
 +420 477 071 500
sales.cz@ligman.com

ASIA PACIFIC

LIGMAN Lighting Co.,Ltd.
 17/2 Moo4 Monthong
 Bangnampreaw
 24150, Chachoengsao
 Thailand
 +66 2 108 6700
info@ligman.com