

Kirium Bollard product codes

	Codes	Example
Family		
Kirium Bollard	KIB	KIB
Style		
Curved	C	C
Angular	A	
Diameter		
160	16	16
200	20	
Colour temperature		
2700K (160 only)	27	30
3000K	30	
4000K	40	
Distribution		
Symmetric	SY	SY
Asymmetric Narrow (200 only)	AN	
Asymmetric Medium	AM	
Asymmetric Wide (200 only)	AW	
180° Shield		
180° light shield	S	N
No light shield	N	
Drive current		
Drive currents from 200mA to 700mA are available in 50mA increments. Insert drive current value in 4-digit format (eg 500mA = 0500).	0200 / 0250 / 0300 / 0350 / 0400 / 0450 / 0500 / 0550 / 0600 / 0650 / 0700	0500
Product colours		
RAL 7046 Mid grey	CF	10
RAL 7035 Light grey	29	
RAL 9005 Black	10	
Mounting		
Root mounted	R	F
Flange mounted	F	
Mounting Accessories (optional)		
Bolt-on root	B	B
Control		
Integral CMS - Urban Control	IUC	IUC
Integral CMS - Telensa	ITE	
Integral CMS - Mayflower	IMA	
<i>Pre-programmed dimming [1]</i>		
Presence detector		
Presence detector (200 diameter only)	PD	PD
Emergency version		
3-hour emergency	EM	
Example code = KIB C 16 30 SY N 0500 10 F B IUC PD		

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)