

Kirium Eco product codes

	Codes	Example
Family		
Kirium Eco Mini	KEM	KEMD
Kirium Eco Midi	KEMD	
Colour temperature		
2200K	22	30
2700K	27	
3000K	30	
4000K	40	
Distribution		
Narrow road	NR	NR
Medium road	MR	
Wide road	WR	
Asymmetric area	AA	
Symmetric area	SA	
Pathway	PW	
Zebra crossing (left hand side)	PXL	
Zebra crossing (right hand side)	PXR	
Drive current		
Drive currents from 250mA to 1050mA are available in 50mA increments. Insert drive current value in 4-digit format (eg 250mA = 0250).	0250 / 0300 / 0350 / 0400 / 0450 / 0500 / 0550 / 0600 / 0650 / 0700 / 0750 / 0800 / 0850 / 0900 / 0950 / 1000 / 1050	0750
Electrical class		
Class I	I	I
Class II	II	
Material		
Full die-cast aluminium (upper and lower)	AL	AL
Hybrid (die cast aluminium upper housing with UV-stabilised polypropylene lower cover)	PP	
Product colours		
RAL 7046 mid grey	CF	CF
RAL 7035 light grey	29	
RAL 9005 black	10	
Control		
No photocell	N	U
Photocell 35 lux (1:0.5)	U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
3 pin NEMA	E	
5 pin NEMA	C3	
7 pin NEMA	D2	
4 pin Zhaga socket	Z4	
Integral CMS - Urban Control	IUC	
Integral CMS - Telensa	ITE	
Integral CMS - Mayflower	IMA	
<i>Pre-programmed dimming [1]</i>		
Example code = KEMD 30 NR 0750 II AL CF U		

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)