

Kirium Pro S product codes

		Codes	Example
Model			
Kirium Pro S1		KPS1	KPS1
	Kirium Pro S2	KPS2	
Light Engine			
16 LED	-	16	24
24 LED	-	24	
32 LED	32 LED	32	
-	48 LED	48	
-	64 LED	64	
Housing			
Full die-cast aluminium		A	A
Die-cast aluminium with polycarbonate lower cover		H	
Mounting			
Universal entry (post top Ø60-76mm / side entry Ø34-60mm) preset for post top		A	A
Universal entry (post top Ø60-76mm / side entry Ø34-60mm) preset for side entry		B	
Dedicated entry (Ø60 - 76mm direct post top)		D	
Dedicated entry (Ø34 - 42mm side entry)		S	
Colour Temperature			
2,700K		27	30
3,000K		30	
4,000K		40	
Light Output			
Drive currents from 200mA to 1050mA are available in 50mA increments. Insert drive current value (eg. 700mA = 700).		200 / 250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	700
Light Distribution			
Wide road - Diamond+ A Optic (A1 / A2 / A3 / A4 / A5)		A1 / A2 / A3 / A4 / A5	A1
Footpath - Diamond+ B Optic (B1 / B2 / B3 / B4 / B5)		B1 / B2 / B3 / B4 / B5	
Area - Diamond+ C Optic (C1 / C2 / C3 / C4 / C5)		C1 / C2 / C3 / C4 / C5	
Standard road - Diamond+ D Optic (D1 / D2 / D3 / D4 / D5)		D1 / D2 / D3 / D4 / D5	
Pedestrian crossing - Diamond+ Z Optic (ZL / ZR / ZF)		ZL / ZR / ZF	
Colour Finish			
RAL 7046 Mid grey		CF	CF
RAL 7035 Light grey		29	
RAL 9005 Black		10	
Other RAL colour (on request)		RAL [specify]	
Paint Finish			
Polyester powder coat		PP	PP
Marine-grade coating		MG	
Connectivity & Control			
No connectivity or control		N	U20
Miniature photocell 20 lux (1:0.5)		U20	
Miniature photocell 20 lux (1:0.5) (top) with 4-pin Zhaga Book 18 socket (bottom)		U20Z	
Miniature photocell 35 lux (1:0.5)		U35	
Miniature photocell 35 lux (1:0.5) (top) with 4-pin Zhaga Book 18 socket (bottom)		U35Z	
6-pin NEMA socket		B1	
7-pin NEMA socket		D2	
7-pin NEMA socket (top) with 4-pin Zhaga Book 18 socket (bottom)		D2Z	
4-pin Zhaga Book 18 socket (top)		Z4	
4-pin Zhaga Book 18 socket (bottom)		Z4A	
4-pin Zhaga Book 18 socket (top and bottom)		Z4B	
Knife Switch (optional)			
Knife switch (electrical disconnection block)		KS	-
Tamper-Proof Screws (optional)			
Tamper-proof screws on toolless entry points		TP	-
Example code = KPS1 24 A A 30 700 A1 CF PP U20			

Light Shields Available on Request

Unglazed version: Front | Rear | Side (L/R)

Glazed version: Front | Rear | Side (L/R)

100mm depth