

## Manhattan product codes

	Codes	Example
<b>Family</b>		
Manhattan	MAN	MAN
<b>Light source</b>		
<b>Performance LED</b>		
16 LED	PL16	PL32
32 LED	PL32	
<b>Colour temperature</b>		
2700K	27	30
3000K	30	
4000K	40	
<b>Distribution<sup>[1]</sup></b>		
Diamond+ A Optic	A1 / A2 / A3 / A4 / A5	A1
Diamond+ B Optic	B1 / B2 / B3 / B4 / B5	
Diamond+ C Optic	C1 / C2 / C3 / C4 / C5	
Diamond+ D Optic	D1 / D2 / D3 / D4 / D5	
Diamond+ Z Optic	ZR / ZL / ZF	
<b>Drive current<sup>[2]</sup></b>		
350mA	0350	0500
500mA	0500	
700mA	0700	
<b>Product colours</b>		
RAL 9016 White	40	20
RAL 9005 Black	10	
RAL 7016 Anthracite grey	20	
RAL 7037 Dusty grey	21	
PAN 7621 Textured metallic silver	81	
RAL 9006 Textured aluminium	26	
RAL 9007 Textured metallic grey	27	
DB 703 Textured metallic dark grey	DB	
<b>Control</b>		
No photocell	N	U
Miniature Photocell 35 lux (1:0.5)	U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
<i>Pre-programmed dimming<sup>[3]</sup></i>		
<i>CMS compatible<sup>[3]</sup></i>		
<i>SR Ready<sup>[3]</sup></i>		
Example code = R15 PL64 30 A1 0500 S 20 U		

<sup>[1]</sup> For further information on Diamond+ visit [dwwindsor.com/diamond](http://dwwindsor.com/diamond)

<sup>[2]</sup> Other than the standard options shown above, drive currents are available in 50mA increments.

<sup>[3]</sup> Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)