

## Milano product codes

		Codes	Example
<b>Family</b>			
Milano		MIL	MIL
<b>Size</b>			
Classic		CL	HA
Halo		HA	
<b>Light engine</b>			
Performance		PE	CO
Comfort		CO	
<b>Colour temperature</b>			
		2400K	27
2700K		2700K	
3000K		3000K	
4000K		40	
<b>Distribution</b>			
Wide road - Diamond+ A Optic (A1)		A1	SY
Footpath - Diamond+ B Optic (B1)		B1	
Area - Diamond+ C Optic - (C2 / C3)		C2 / C3	
Standard road - Diamond+ D Optic (D1)		D1	
		Symmetric	
<b>Drive current</b>			
<p>The Performance engine is constant current and can be run at drive currents from 75mA to 800mA are available in 25mA increments. The Comfort engine is constant voltage and can be dimmed down from full output (100%). 25% is 25% of initial output.</p>			080
Insert drive current in 3-digit format		eg 250mA = 250	
		Insert output percentage in 3-digit format eg 40% = 040	
<b>Product colours</b>			
RAL 9016 White		40	DB
RAL 9005 Black		10	
RAL 9006 Aluminium		26	
RAL 9007 Metallic grey		27	
DB 703 Metallic dark grey		DB	
Corten brown		CB	
<b>Control</b>			
No photocell		N	IUC
Miniature Photocell 35 lux (1:0.5)		U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)		A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)		D8	
Integral CMS - Urban Control (Classic & Halo)		IUC	
Integral CMS - Telensa (Classic only)		ITE	
Integral CMS - Mayflower (Classic only)		IMA	
5 pin NEMA (Halo only)		C3	
7 pin NEMA (Halo only)		D2	
<i>Pre-programmed dimming [1]</i>			
<b>Example code = MIL HA CO 27 SY 080 DB IUC</b>			

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)