

## Milano product codes

	Codes	Example
<b>Family</b>		
Milano	MIL	MIL
<b>Model</b>		
Curved Arms	C	C
Straight Arms	S	
<b>Light Engine</b>		
4 LED	4	32
8 LED	8	
16 LED	16	
32 LED	32	
<b>Colour Temperature</b>		
2700K	27	30
3000K	30	
4000K	40	
<b>Drive Current</b>		
<p>Drive currents from 250mA to 1000mA are available in 50mA increments.            Insert drive current value (eg. 750mA = 750).</p>	0250 / 0300 / 0350 / 0400 / 0450 / 0500 / 0550 / 0600 / 0650 / 0700 / 0750 / 0800 / 0850 / 0900 / 0950 / 1000	700
<b>Distribution<sup>[1]</sup></b>		
Wide road - Diamond+ A Optic (A1 / A2 / A3 / A4 / A5)	A1 / A2 / A3 / A4 / A5	A1
Footpath - Diamond+ B Optic (B1 / B2 / B3 / B4 / B5)	B1 / B2 / B3 / B4 / B5	
Area - Diamond+ C Optic (C1 / C2 / C3 / C4 / C5)	C1 / C2 / C3 / C4 / C5	
Standard road - Diamond+ D Optic (D1 / D2 / D3 / D4 / D5)	D1 / D2 / D3 / D4 / D5	
<b>Glazing</b>		
Flat Glass	EG	EG
Clear Polycarbonate Bowl	CA	
<b>Housing Colour</b>		
RAL 9016 White	40	20
RAL 9005 Black	10	
RAL 7016 Anthracite grey	20	
RAL 7037 Dusty grey	21	
PAN 7621 Metallic silver	81	
RAL 9006 Textured aluminium	26	
RAL 9007 Textured metallic grey	27	
DB 703 Textured metallic dark grey	DB	
<b>Control</b>		
No photocell	N	U
Miniature Photocell 35 lux (1:0.5)	U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
<i>Pre-programmed dimming</i> <sup>[2]</sup>		
<i>CMS compatible</i> <sup>[2]</sup>		
<i>SR Ready</i> <sup>[2]</sup>		
<b>Example code = MIL C 32 30 700 A1 EG 20 U</b>		

[1] For further information on Diamond+ visit [dwwindsor.com/diamond](http://dwwindsor.com/diamond)

[2] Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)