

For Installation of Nikon recessed exterior downlight round dia 200mm. and square 200mm. LED.  
 Model. NI-80521, NI-80523, NI-80525 and NI-80531, NI-80533, NI-80535

**Product drawing (dimensions)**

CE IP65 IK08 CLASS I 0.5m

TOOL

NI-80521, NI-80523  
NI-80525

NI-80531, NI-80533  
NI-80535

1. Preparing the ceiling and mounting the base.

2. CEILING CUT HOLE Ø184mm. MAIN CABLE POWER SUPPLY OD MIN. 6mm. MAX. 12mm.

3. Torque :0.25Nm. Connecting the power supply (N, L, GND).

4. Torque :3.0Nm. Tightening the base.

5. Mounting the LED module.

6. Mounting the diffuser.

7. Torque :3.0Nm. Tightening the diffuser.

8. Torque :3.0Nm. Tightening the outer ring.

9. Final view of the installed downlight.

- LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz. The control gear for other voltages and frequencies is available upon request, please consult us for more details.
- LIGMAN luminaires are designed to conform IEC 60598 2-2 standard.

Technical amendments and modifications techniques reserved.

## Ligman Lighting

**Europe Headquarters**  
 Ligman Europe s.r.o.  
 VGP Park Usti nad Labem, P 2  
 Prestanov 113  
 403 17 Prestanov  
 Czech Republic  
 Tel. +420 608 740 504 | sales.cz@ligman.com

**Thailand Headquarters**  
 Ligman Lighting Co., Ltd.  
 17/2 Moo 4, Monthong, Bangnampreaw  
 Chachoengsao 24150 Thailand  
 Tel : +66 (2) 7339140  
 info@ligman.com

**Ligman SAS France**  
 7 rue Antoine Becquerel  
 Centre d'activités Trisis  
 31140, Launaguet  
 Tel: +33 5 61 70 24 62  
 sales.fr@ligman.com