

Sabre product codes

		Codes	Example
Model			
Sabre 1		SA1	SA2
	Sabre 2	SA2	
	Sabre 3	SA3	
LED quantity			
16 LED		016	032
	24 LED	024	
	32 LED	032	
	64 LED	064	
Mounting			
Stirrup bracket (standard)		R	R
Ø76mm Post top		PT	
Colour temperature			
2700K		27	40
3000K		30	
4000K		40	
Distribution			
Asymmetric - narrow (Diamond+ Optic B1)		B1	F1
Asymmetric - medium (Diamond+ Optic A1)		A1	
Asymmetric - wide (Diamond+ Optic C2)		C2	
Symmetric (Diamond+ Optic C3)		C3	
Wide flood (Diamond+ Optic F1)		F1	
Product colours			
RAL 7046 Mid grey		CF	CF
Control			
No photocell		N	IUC
Photocell 35 lux (1:0.5)		U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)		A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)		D8	
3 pin NEMA		E	
5 pin NEMA		C3	
7 pin NEMA		D2	
4 pin Zhaga socket		Z4	
Integral CMS - Urban Control (Sabre 2 & 3 only)		IUC	
Integral CMS - Telensa (Sabre 2 & 3 only)		ITE	
Integral CMS - Mayflower (Sabre 2 & 3 only)		IMA	
<i>Pre-programmed dimming [1]</i>			
Presence detector			
Presence detector		PD	
Example code = SA2 032 R 40 F1 CF IUC			

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)