

Sephora Catenary & Pendant product codes

		Codes	Example
Family			
Sephora		SEP	SEP
Style			
Radius		RA	RA
Cubis		CU	
Mounting			
Catenary Hanger		CAT	CAT
Pendant Easyfit™		PEN	
Light engine			
Performance		PE	CO
Comfort		CO	
Colour temperature			
2400K		24	27
2700K		27	
3000K		30	
4000K		40	
Distribution			
Wide road - Diamond+ A Optic (A1)		A1	SY
Footpath - Diamond+ B Optic (B1)		B1	
Area - Diamond+ C Optic (C3)		C3	
Standard road - Diamond+ D Optic (D1)		D1	
Symmetric		SY	
Drive current			
The Performance engine is constant current and can be run at drive currents from 75mA to 800mA are available in 25mA increments. The Comfort engine is constant voltage and can be dimmed down from full output (100%). 25% is 25% of initial output.			080
Insert drive current in 3-digit format		eg 250mA = 250	
Insert output percentage in 3-digit format		eg 40% = 040	
Product colours			
RAL 9016 White		40	DB
RAL 9005 Black		10	
RAL 9006 Aluminium		26	
RAL 9007 Metallic grey		27	
DB 703 Metallic dark grey		DB	
Corten brown		CB	
Control			
No photocell		N	IUC
Photocell 35 lux (1:0.5)		U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)		A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)		D8	
Integral CMS - Urban Control		IUC	
Integral CMS - Telensa		ITE	
Integral CMS - Mayflower		IMA	
<i>Pre-programmed dimming [1]</i>			
Example code = SEP RA CAT CO 27 SY 080 DB IUC			

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)