

Sephora product codes

					Codes	Example	
Family							
Sephora					SEP	SEP	
Style							
Radius					RA	RA	
Cubis					CU		
Size							
450					45		
				650	65	HA	
				Halo	HA		
Mounting							
Ø42 Side entry		Ø42 Side entry		Ø42 Side entry		42SE	CDPI
Ø76 Direct post		Ø76 Direct post		Ø76 Direct post		76DP	
Ø76 Post top						76PT	
		Ø114 Post top				11PT	
				Curved direct post (internal)		CDPI	
				Curved direct post (external)		CDPE	
Light engine							
Performance		Performance		Performance		PE	CO
Comfort				Comfort		CO	
Colour temperature							
2200K				2200K		22	27
2700K		2700K		2700K		27	
3000K		3000K		3000K		30	
4000K		4000K		4000K		40	
Distribution							
Diamond+ Optic - A1		Diamond+ Optic - A1		Diamond+ Optic - A1		A1	SY
Diamond+ Optic - B1		Diamond+ Optic - B1		Diamond+ Optic - B1		B1	
Diamond+ Optic - C2		Diamond+ Optic - C2		Diamond+ Optic - C2		C2	
Diamond+ Optic - C3		Diamond+ Optic - C3		Diamond+ Optic - C3		C3	
Diamond+ Optic - D1		Diamond+ Optic - D1		Diamond+ Optic - D1		D1	
		Symmetric		Symmetric		SY	
Drive current							
The Performance engine is constant current and can be run at drive currents from 75mA to 800mA are available in 25mA increments. The Comfort engine is constant voltage and can be dimmed down from full output (100%). 25% is 25% of initial output.							
Insert drive current in 3-digit format		Insert drive current in 3-digit format		Insert drive current in 3-digit format		eg 250mA = 250	080
		Insert output percentage in 3-digit format		Insert output percentage in 3-digit format		eg 40% = 040	
Product colours							
RAL 9016 White					40	DB	
RAL 9005 Black					10		
RAL 9006 Aluminium					26		
RAL 9007 Metallic grey					27		
DB 703 Metallic dark grey					DB		
Corten brown					CB		
Control							
No photocell					N	A4	
Photocell 35 lux (1:0.5)					U		
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)					A4		
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)					D8		
3 pin NEMA					E		
5 pin NEMA					C3		
7 pin NEMA					D2		
<i>Pre-programmed dimming [1]</i>							
<i>CMS compatible [1]</i>							
<i>SR Ready [1]</i>							
Example code = SEP RA HA CDPI CO 27 SY 080 DB A4							

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)