Strand product codes

													Codes	Example
Model														
Strand A Plus													SAP	SA
	Strand A												SA	
				Strand B									SB	
								Strand C					SC	
Mounting														
Pendant Easyfit™		Pendant Easyfit™			Pendant Easyfit™				Pendant Easyfit™				E	E
	Pendant Threaded				Pendant Threaded				Pendant Threaded				T	
					U bracket square				U bracket square				UBS	
					U bracket tear drop				U bracket tear drop				UBT	
Brim														
Wide		Wide			Wide				Wide				W	W
	Narrow				Narrow				Narrow				N	
Light source														
Performance LED		Performance LED			Performance LED				Performance LED					PL64
					16 LED				16 LED				PL16	
32 LED		32 LED			32 LED								PL32	
64 LED		64 LED											PL64	
75 LED													PL75	
96 LED													PL96	
			Performance CoB			Performance CoB				Performance CoB				
			Single CoB			Single CoB				Single CoB			PC01	
							Comfort CoB				Comfort CoB			
							Single CoB				Single CoB		CC01	
	Lamp: SON-T / CDO-TT			Lamp: SON-T / CDO-TT				Lamp: SON-T / CDO-TT				Lamp: SON-T+ / CDO-TT		
												50W	050S	
								70W				70W	070S	
				100W				100W					100S	
				150W									150S	
	250W												250S	
				Lamp: CosmoPolis				Lamp: CosmoPolis				Lamp: CosmoPolis		
								45W				45W	045W	
								60W					060W	
				90W				90W					090W	
				140W									140W	
Colour temperature														
2700K	n/a	2700K	2700K	n/a	2700K	2700K	2700K	n/a	2700K	2700K	2700K	n/a	27	30
3000K		3000K	3000K		3000K	3000K	3000K		3000K	3000K	3000K		30	
4000K		4000K	4000K		4000K	4000K			4000K	4000K			40	
Distribution[1]														
Diamond+ A Optic		Diamond+ A Optic			Diamond+ A Optic				Diamond+ A Optic				A1 / A2 / A3 / A4 / A5	A1
Diamond+ B Optic		Diamond+ B Optic			Diamond+ B Optic				Diamond+ B Optic				B1 / B2 / B3 / B4 / B5	
Diamond+ C Optic		Diamond+ C Optic			Diamond+ C Optic				Diamond+ C Optic				C1 / C2 / C3 / C4 / C5	
Diamond+ D Optic		Diamond+ D Optic			Diamond+ D Optic				Diamond+ D Optic				D1 / D2 / D3 / D4 / D5	
Diamond+ Z Optic		Diamond+ Z Optic			Diamond+ Z Optic				Diamond+ Z Optic				ZR / ZL / ZF	
			A1			A1				A1			A1	
			B1			B1				B1			B1	
			C1			C1				C1			C1	
			D1			D1				D1			D1	
							Symmetric				Symmetric		SY	
	5/35 - A			5/35 - A				5/35 - A				5/35 - A	A	
	10/10 - B			10/10 - B				10/10 - B				10/10 - B	B	
	31/35 - C			31/35 - C				31/35 - C				31/35 - C	C	
	5/25 - D			5/25 - D				5/25 - D				5/25 - D	D	
Drive current[2]														
350mA	n/a	350mA		n/a	350mA			n/a	350mA			n/a	0350	1000
500mA		500mA			500mA				500mA				0500	
700mA		700mA			700mA				700mA				0700	
1000mA		1000mA											1000	
Product colours														
RAL 9005 Black													10	10
RAL 7016 Anthracite grey													20	
RAL 7037 Dusty grey													21	
RAL 5003 Sapphire blue													30	
RAL 6005 Light moss green													50	
RAL 3005 Wine red													70	
Control														
No photocell													N	A4
Miniature Photocell 35 lux (1:0.5)													U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)													A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)													D8	
Integral CMS - Urban Control (Strand A Plus, A & B only)													IUC	
Integral CMS - Telensa (Strand A Plus, A & B only)													ITE	
Integral CMS - Mayflower (Strand A Plus, A & B only)													IMA	
Pre-programmed dimming [3]														
SR Ready [3]														

Example code = SA E W PL64 30 A1 1000 10 A4

[1] For further information on Diamond+ visit dwwindsor.com/diamond

[2] Other than the standard options shown above, drive currents are available in 50mA increments.

[3]Available as standard subject to further information being provided at time of order.

For further help specifying a product, please contact us

DW Windsor
Pindar Road, Hoddesdon, Hertfordshire, EN11 0DX
T: +44 (0)1992 474600 | E: info@dwwindsor.com
dwwindsor.com