

Stratum product codes

	Codes	Example
Model		
Stratum 450	ST4	ST4
Stratum 500	ST5	
Light source		
Performance LED		
16 LED	PL16	PL32
32 LED	PL32	
64 LED	PL64	
Colour temperature		
2700K	27	30
3000K	30	
4000K	40	
Distribution^[1]		
Diamond+ A Optic	A1 / A2 / A3 / A4 / A5	A1
Diamond+ B Optic	B1 / B2 / B3 / B4 / B5	
Diamond+ C Optic	C1 / C2 / C3 / C4 / C5	
Diamond+ D Optic	D1 / D2 / D3 / D4 / D5	
Diamond+ Z Optic	ZR / ZL / ZF	
Drive current^[2]		
350mA	O350	O500
500mA	O500	
700mA	O700	
Mounting		
Direct Post	D	D
Side Entry	S	
Pendant Easyfit™	E	
Pendant Threaded	T	
Glazing		
Flat toughened glass	FG	PB
Polycarbonate bowl	PB	
Product colours		
RAL 9005 Black	10	20
RAL 7016 Anthracite grey	20	
RAL 7037 Dusty grey	21	
RAL 9007 Textured metallic grey	27	
RAL 5003 Sapphire blue	30	
RAL 6005 Light moss green	50	
Control		
No photocell	N	U
Miniature Photocell 35 lux (1:0.5)	U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
<i>Pre-programmed dimming</i> ^[3]		
<i>CMS compatible</i> ^[3]		
<i>SR Ready</i> ^[3]		
Example code = ST4 PL32 30 A1 O500 D PB 20 U		

^[1] For further information on Diamond+ visit dwindsor.com/diamond

^[2] Other than the standard options shown above, drive currents are available in 50mA increments.

^[3] Available as standard subject to further information being provided at time of order.

For further help specifying a product, please [contact us](#)