



Sample Specification Text

Aventis Eyelid wall luminaire with LED light engine and output of 2,100lm with 3,000K colour temperature. Fixed output DALI driver operating at 500mA. Die-cast aluminium body in RAL 7046 mid grey with a polyester powder coat finish and frosted polycarbonate glazing. IP65 and IK08 protection. For -25 °C to +40 °C ambient operating temperatures. Class I.

Performance

Output (luminaire flux)	2,100lm (max)
Power	19W (max)
Efficacy	111lm/W (max)
Colour Temperatures	3000K 4000K
Colour Rendering Index (CRI)	> 80
Distributions	Symmetric
Certifications	UKCA, CE

Mechanical

Mounting Options	Wall mount
Glazing	Frosted polycarbonate
Housing	Die-cast aluminium
Colours	Mid Grey RAL 7046 Black RAL 9005
Finish	Polyester powder coat Marine-grade C4 coating
IP Rating	IP65
IK Rating	IK08
Weight	2.5kg

Electrical

Driver Options	DALI
Drive Current Range	300mA 500mA
Operating Voltage	220-240V
Electrical Class	Class I Class II (on request)
Operating Temperature Limit	-25 °C to +40 °C

Control

Control Options	Photocell Integral CMS Presence detector Integral 3-hour emergency
------------------------	---