

Grey Wornum product codes

		Codes	Examp	
Model				
Small Grey Wornum		SGW	sgw	
	Large Grey Wornum	LGW	SGW	
Mounting				
Pendant Easyfit™	-	E	LIDO	
Cast U-bracket	Cast U-bracket	UBC	UBC	
Light Engine				
Performance LED				
16 LED	-	16		
24 LED	-	24	04	
32 LED	-	32	24	
-	48 LED	48		
-	64 LED	64		
Colour Temperature				
2700K	OK			
3000K			30	
4000K		30 40		
Light Distribution				
Roads - Diamond+ A Optic		A1/A2/A3/A5/A6		
Pathways - Diamond+ B Optic		B1/B2/B3	A1	
Areas - Diamond+ C Optic		C1/C2/C6		
Drive Current (Output)				
		250/300/350/400/450/		
Duit to accompanie from OFO as A to				
Drive currents from 250mA to 1050mA are available in 50mA increments Insert drive current value (e.g. 700mA = 700)		500/550/600/650/700/	700	
		750/800/850/900/950/		
		1000 / 1050		
Colour Finish				
RAL 9005 black		10	10	
Other RAL colours on request		RAL [specify]	10	
Control (optional)				
Miniature Photocell 20 lux (1:1)		20L	UAC	
liniature Photocell 35 lux (1:0.5)		35L		
4-pin Zhaga Book 18 socket (top)		Z4		
ntegral CMS - Urban Control (AC node with puck antenna)		UAC		
Integral CMS - Urban Control (DC node with puck antenna) UDC				
Integral CMS - Telensa (with monopole antenna)		TEL		
Integral CMS - Mayflower (with stub antenna)		MAY		

For further help specifying a product, please contact us