

Knightsbridge product codes

			Codes	Example
Model				
Knightsbridge Street			KNS	KNS
Knightsbridge Avenue			KNA	
Light Engine				
Performance LED				
16 LED			16	PC
24 LED			24	
32 LED			32	
Performance CoB				
Single CoB			PC	
Comfort CoB				
Single CoB			CC	
Colour Temperature				
2700K	2700K	2700K	27	27
3000K	3000K	3000K	30	
4000K	4000K		40	
Distribution				
Roads - Diamond+ A Optic			A1 / A2 / A3 / A5 / A6	A1
Pathways - Diamond+ B Optic			B1 / B2 / B3	
Areas - Diamond+ C Optic			C1 / C2 / C6	
Wide Roads - AC1			AC1	
Pathways BC1			BC1	
Areas - CC1			CC1	
Roads - DC1			DC1	
			Symmetric	SY
Drive Current				
Drive currents from 250mA to 1050mA are available in 50mA increments Insert drive current value (eg 750mA = 750)			250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	500
Product Colours				
RAL 9005 Black			10	10
RAL 7016 Anthracite grey			20	
RAL 7037 Dusty grey			21	
RAL 5003 Sapphire blue			30	
RAL 6005 Light moss green			50	
RAL 3005 Wine red			70	
Natural copper finish			02	
Polished and lacquered copper finish			03	
Control				
No photocell			N	U
Miniature Photocell 35 lux (1:0.5)			U	
Part night switching miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)			A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)			D8	
Integral CMS - Urban Control			IUC	
Integral CMS - Telensa			ITE	
Integral CMS - Mayflower			IMA	
Pre-programmed dimming				
D4i/SR Ready				
Example code = KNS PC 27 A1 500 10 U				

For further help specifying a product, please [contact us](#)