

## Milano Classic and Halo product codes

	Codes	Example
<b>Family</b>		
Milano	MIL	MIL
<b>Size</b>		
Classic	CL	HA
Halo	HA	
<b>Light Engine</b>		
Performance	PE	PE
<b>Colour Temperature</b>		
2700K	27	30
3000K	30	
4000K	40	
<b>Distribution</b>		
Roads - Diamond+ A Optic (A1)	A1	A1
Pathways - Diamond+ B Optic (B1)	B1	
Areas - Diamond+ C Optic - (C2 / C3)	C2 / C3	
<b>Drive Current</b>		
<p>The Performance engine is constant current and can be run at drive currents from 200mA to 800mA are available in 50mA increments.</p> <p>Insert drive current value (eg. 700mA = 700)</p>		700
<b>Product Colours</b>		
RAL 9016 White	40	DB
RAL 9005 Black	10	
RAL 9006 Aluminium	26	
RAL 9007 Metallic grey	27	
DB 703 Metallic dark grey	DB	
Corten brown	CB	
<b>Control</b>		
No photocell	N	IUC
Miniature Photocell 35 lux (1:0.5)	U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
Integral CMS - Urban Control (Classic & Halo)	IUC	
Integral CMS - Telensa (Classic only)	ITE	
Integral CMS - Mayflower (Classic only)	IMA	
5 pin NEMA (Halo only)	C3	
7 pin NEMA (Halo only)	D2	
<i>Pre-programmed dimming</i>		
<i>D4i/SR Ready</i>		
<b>Example code = MIL HA PE 30 A1 700 DB IUC</b>		

For further help with specifying a product, please [contact us](#)