

Milano Original product codes

	Codes	Example
Family		
Milano Original	MIL	MIL
Model		
Curved Arms	C	C
Straight Arms	S	
Light Engine		
8 LED	8	32
16 LED	16	
32 LED	32	
Colour Temperature		
2700K	27	30
3000K	30	
4000K	40	
Drive Current		
Drive currents from 250mA to 1050mA are available in 50mA increments Insert drive current value (eg 750mA = 750)	250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	700
Distribution⁽¹⁾		
Roads - Diamond+ A Optic	A1 / A2 / A3 / A5 / A6	A1
Pathways - Diamond+ B Optic	B1 / B2 / B3	
Areas - Diamond+ C Optic	C1 / C2 / C6	
Housing Colour		
RAL 9016 White	40	20
RAL 9005 Black	10	
RAL 7016 Anthracite grey	20	
RAL 7037 Dusty grey	21	
RAL 9006 Textured aluminium	26	
RAL 9007 Textured metallic grey	27	
DB 703 Textured metallic dark grey	DB	
Control		
No photocell	N	U
Miniature Photocell 35 lux (1:0.5)	U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
<i>Pre-programmed dimming</i>		
<i>D4i/SR Ready</i>		
<i>CMS compatible</i>		
Example code = MIL C 32 30 700 A1 20 U		

For further help specifying a product, please [contact us](#)