

Pall Mall product codes

			Codes	Example
Family				
Pall Mall			PMS	PMS
Light Engine				
Performance LED				
8 LED			8	16
16 LED			16	
24 LED			24	
32 LED			32	
Performance CoB				
Single CoB			PC	
Comfort CoB				
Single CoB			CC	
Colour Temperature				
2700K	2700K	2700K	27	27
3000K	3000K	3000K	30	
4000K	4000K		40	
Distribution				
Roads - Diamond+ A Optic			A1 / A2 / A3 / A5 / A6	B1
Pathways - Diamond+ B Optic			B1 / B2 / B3	
Areas - Diamond+ C Optic			C1 / C2 / C6	
	Wide Roads - AC1		AC1	
	Pathways BC1		BC1	
	Areas - CC1		CC1	
	Roads - DC1		DC1	
		Symmetric	SY	
Drive Current				
Drive currents from 250mA to 1050mA are available in 50mA increments Insert drive current value (eg 750mA = 750)			250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	500
Product Colours				
RAL 9005 Black			10	10
RAL 7016 Anthracite grey			20	
RAL 7037 Dusty grey			21	
RAL 5003 Sapphire blue			30	
RAL 6005 Light moss green			50	
RAL 3005 Wine red			70	
Natural copper finish			02	
Polished and lacquered copper finish			03	
Control				
No photocell			N	U
Miniature Photocell 35 lux (1:0.5)			U	
Part night switching miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)			A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)			D8	
Integral CMS - Urban Control			IUC	
Integral CMS - Telensa			ITE	
Integral CMS - Mayflower			IMA	
<i>Pre-programmed dimming</i>				
<i>D4/SR Ready</i>				
Example code = PMS 16 27 B1 500 10 U				

For further help specifying a product, please [contact us](#)