

Strand product codes

Model									Codes	Example
Strand A Plus									SAP	SA
Strand A									SA	
Strand B									SB	
Strand C									SC	
Mounting										E
Pendant Easyfit™		Pendant Easyfit™		Pendant Easyfit™		Pendant Easyfit™			E	
Pendant Threaded		Pendant Threaded		Pendant Threaded		Pendant Threaded			T	
		U bracket square		U bracket square		U bracket square			UBS	
		U bracket tear drop		U bracket tear drop		U bracket tear drop			UBT	
Light Engine										64
Performance LED		Performance LED		Performance LED		Performance LED			8	
16 LED		16 LED		16 LED		16 LED			16	
		24 LED							24	
32 LED		32 LED							32	
48 LED		48 LED							48	
64 LED		64 LED							64	
96 LED									96	
		Performance CoB		Performance CoB		Performance CoB				
		Single CoB		Single CoB		Single CoB			PC	
				Comfort CoB		Comfort CoB				
				Single CoB		Single CoB			CC	
Colour Temperature										30
2700K		2700K		2700K		2700K			27	
3000K		3000K		3000K		3000K			30	
4000K		4000K		4000K		4000K			40	
Distribution										A1
Roads - Diamond+ A Optic		Roads - Diamond+ A Optic		Roads - Diamond+ A Optic		Roads - Diamond+ A Optic			A1 / A2 / A3 / A5 / A6	
Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic			B1 / B2 / B3	
Areas - Diamond+ C Optic		Areas - Diamond+ C Optic		Areas - Diamond+ C Optic		Areas - Diamond+ C Optic			C1 / C2 / C6	
Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic			ZR / ZL / ZF	
		Wide Roads - AC1		Wide Roads - AC1		Wide Roads - AC1			AC1	
		Pathways BC1		Pathways BC1		Pathways BC1			BC1	
		Areas - CC1		Areas - CC1		Areas - CC1			CC1	
		Roads - DC1		Roads - DC1		Roads - DC1			DC1	
				Symmetric		Symmetric			SY	
Drive Current										700
<p>Drive currents from 250mA to 1000mA are available in 50mA increments Insert drive current value (eg 750mA = 750)</p> <p>Notes Strand A Plus = 700mA maximum Strand A = 900mA maximum</p>									250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	
Product Colours										10
RAL 9005 Black									10	
RAL 7016 Anthracite grey									20	
RAL 7037 Dusty grey									21	
RAL 5003 Sapphire blue									30	
RAL 6005 Light moss green									50	
RAL 3005 Wine red									70	
Control										A4
No photocell									N	
Miniature Photocell 35 lux (1:0.5)									U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)									A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)									D8	
Integral CMS - Urban Control (Strand A Plus, A & B only)									IUC	
Integral CMS - Telensa (Strand A Plus, A & B only)									ITE	
Integral CMS - Mayflower (Strand A Plus, A & B only)									IMA	
Pre-programmed dimming										
D4/SR Ready										
Example code = SA E 64 30 A1 700 10 A4										