

Strand product codes

										Codes	Example
<b>Model</b>											
Strand A Plus										SAP	SA
Strand A										SA	
		Strand B								SB	
		Strand B DS (2700K and 3000K Performance LED only)								SBDS	
										Strand C	SC
<b>Mounting</b>											
Pendant Easyfit™		Pendant Easyfit™		Pendant Easyfit™		Pendant Easyfit™				E	E
		Pendant Threaded		Pendant Threaded		Pendant Threaded				T	
				U bracket square		U bracket square				UBS	
				U bracket tear drop		U bracket tear drop				UBT	
<b>Light Engine</b>											
Performance LED		Performance LED		Performance LED		Performance LED					64
				8 LED		8 LED				8	
		16 LED		16 LED		16 LED				16	
				24 LED						24	
32 LED		32 LED		32 LED						32	
48 LED		48 LED								48	
64 LED		64 LED								64	
96 LED										96	
		Performance CoB		Performance CoB		Performance CoB					
		Single CoB		Single CoB		Single CoB				PC	
				Comfort CoB		Comfort CoB					
				Single CoB		Single CoB				CC	
<b>Colour Temperature</b>											
2700K		2700K		2700K		2700K		2700K		27	30
3000K		3000K		3000K		3000K		3000K		30	
4000K		4000K		4000K		4000K		4000K		40	
<b>Distribution</b>											
Roads - Diamond+ A Optic		Roads - Diamond+ A Optic		Roads - Diamond+ A Optic		Roads - Diamond+ A Optic				A1 / A2 / A3 / A5 / A6	A1
Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic		Pathways - Diamond+ B Optic				B1 / B2 / B3	
Areas - Diamond+ C Optic		Areas - Diamond+ C Optic		Areas - Diamond+ C Optic		Areas - Diamond+ C Optic				C1 / C2 / C6	
Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic		Crossings - Diamond+ Z Optic				ZR / ZL / ZF	
		Wide Roads - AC1		Wide Roads - AC1		Wide Roads - AC1				AC1	
		Pathways BC1		Pathways BC1		Pathways BC1				BC1	
		Areas - CC1		Areas - CC1		Areas - CC1				CC1	
		Roads - DC1		Roads - DC1		Roads - DC1				DC1	
				Symmetric		Symmetric				SY	
<b>Drive Current</b>											
<p>Drive currents from 250mA to 1000mA are available in 50mA increments            Insert drive current value (eg 750mA = 750)</p> <p><b>Notes</b>            Strand A Plus (96 LED) = 700mA maximum            Strand A (64 LED) = 900mA maximum</p>										250 / 300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 950 / 1000 / 1050	700
<b>Product Colours</b>											
RAL 9005 Black										10	10
RAL 7016 Anthracite grey										20	
RAL 7037 Dusty grey										21	
RAL 5003 Sapphire blue										30	
RAL 6005 Light moss green										50	
RAL 3005 Wine red										70	
<b>Control</b>											
No photocell										N	A4
Miniature Photocell 35 lux (1:0.5)										U	
Part night switching Miniature Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)										A4	
Miniature Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)										D8	
Integral CMS - Urban Control (Strand A Plus, A & B only)										IUC	
Integral CMS - Telensa (Strand A Plus, A & B only)										ITE	
Integral CMS - Mayflower (Strand A Plus, A & B only)										IMA	
<i>Pre-programmed dimming</i>											
<i>D4/SR Ready</i>											
<b>Example code = SA E 64 30 A1 700 10 A4</b>											